




FRIIA CHILLER/ CARBONATOR

- > Cold and/or sparkling: 7.9-11.8 GALS/hr
 - External CO₂ required
 - Aluminium block cooling technology
- > Suitable for: Offices, Hotels, Transport, Institutions, Cafes

CHILLER/CARBONATOR 1001053US/1001052US



SYSTEM SET-UP for Cold/Sparkling



SPECS

PRODUCT INFO	SIZE	PERFORMANCE SPECS		PLUMBING, ELECTRICAL & TECHNICAL SPECS			
NAME ORDER CODE	DIMS (D X W X H inch)	L/HR	CUPS /HR	POWER @120v	PLUMBING REQS	COMPRESSOR POWER	REFRIGERANT
FRIIA Chiller 1001053US FRIIA Carbonator 1001052US	19.6 x 11.1 x 16.6	7.9-11.8 GALS/hr based on incoming water temp of 59°F and output water temp of 41-44°F	175-235 ($\Delta T = 18^\circ F$)	180 W	Compression or 3/8" John Guest	1/8hp	R290

A minimum operating pressure of 2 bar or 28 psi downstream of filter is required for optimum output l/min.

PACKAGING

NAME	DIMENSIONS (L X W X H inch)	WEIGHT	QTY PER PALLET
FRIIA Chiller/Carbonator	15.7 x 23.6 x 22.8	69.4lbs	8